



**ZONE I M1**

## IS930.M1

The IS930.M1 is the tablet for use in ATEX, IECEx and ANZEx Zone I M1.

The 8" tablet is highly robust, powerful and offers many technical advantages: 8.400 mAh Battery, Qualcomm Snapdragon SDM 660, NFC, Android™ 9.

› Please visit our website and you will find more detailed information, as well as an overview of compatible accessories. › i.safe MOBILE and i.safe MOBILE logo are registered trademarks of i.safe MOBILE GmbH. Android is a trademark of Google LLC. The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License. Bluetooth® is a registered trademark of Bluetooth SIG, Inc. worldwide. Wi-Fi® is a registered trademark of the Wi-Fi Alliance. All other trademarks and copyrights are the properties of their respective owners. › © 2020 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1030MD03REV00\_EN\_09.2020

## TECHNICAL FEATURES



Homologation ATEX :  
 Ⓢ I M1 Ex ia I Ma IP64



Homologation IECEx :  
 Ex ia I Ma IP64



Homologation ANZEx :  
 Ex ia I Ma  
 -20 °C ≤ Ta ≤ +60 °C



Android 9



2,4GHz + 5GHz: IEEE  
 802.11a/ b/g/n/ac/e/k/r/h  
 with max. 8 connections  
 hotspot



GSM 850/900/1800/  
 1900 MHz  
 WCDMA: UMTS B1/2/4/5/8  
 LTE-TDD: B38/B39/B40/B41  
 LTE-FDD: B1/2/3/4/5/7/8/12  
 with MFBI B13/14/17/20/25/  
 26/28A/28B/29/30/66  
 TD-SCDMA: B34/B39



Bluetooth® 5



size: 237 x 156 x 22 mm,  
 weight: 890 g



external memory  
 microSD up to 128 GB



Near Field  
 Communication



Qualcomm Snapdragon  
 SDM660 Octa-Core  
 Kryo Gold-Quad cores  
 2.2GHz  
 Kryo Silver-Quad cores  
 1.8GHz  
 4 GB RAM  
 64 GB internal memory



magnetic charging port



2 cameras:  
 13 MP AF rear camera and  
 5 MP front camera



SOS-key  
 Loneworker protection  
 LWP ready (third party  
 application required,  
 based on country specific  
 regulations)

## FURTHER FEATURES



waterproof: 1 hour  
 up to 2 m, impervious to  
 dust and microparticles



operation range from  
 -20 °C to 60 °C



8" multi capacitive touch-  
 screen with a resolution  
 of 1200 x 1920 pixel,  
 RugDisplay-Glass



usable with gloves



8.400 mAh battery



GPS, A-GPS, Glonass,  
 Beidou, Galileo



Proximity, acceleration,  
 light, barometer and  
 magnetic sensor

## SET CONTENT

Tablet with integrated battery, charger, i.safe PROTECTOR 2.0 USB cable,  
 i.safe PROTECTOR 3.0 USB cable, quick start manual and safety instructions